

Yato | Code YT-82076 | Sku 1082076

## Drywall Screwdriver 18V - Body Only



### Overview

The cordless drywall screwdriver is designed for professionals and advanced users who require a reliable tool for working with plasterboard, wood, and wood-based materials. It provides efficiency, speed, and repeatable precision during assembly while maintaining modern ergonomic principles and high-quality workmanship. Thanks to electronic speed control and rotation direction adjustment, it allows you to tailor work parameters to the type of material and screw length. It significantly reduces time spent on installations in attics, suspended ceilings, and partition walls made of plasterboard. Key features: Rotational speed up to 4000 rpm ensures rapid driving of screws with a diameter of 3.5–4.2 mm and a length of 25–55 mm. The tool's light weight (1.49 kg) and compact design minimize fatigue even during prolonged use, maintaining ergonomics and work comfort. The cordless 18 V Li-Ion design provides mobility and long working time without interruptions. The battery charge indicator allows continuous monitoring of available energy. Versatile application thanks to compatibility with both collated tape screws and individual screws. Attachments and adapters increase flexibility across various projects. Solid construction guarantees durability and safety during daily intensive use. The 1/4" (6.3 mm) hexagonal chuck and speed adjustment allow full control over torque and screw depth. Available versions: YT-82075 – with 4 Ah battery and fast 2-hour charger; YT-82076 – body only (no battery).

### Key Technical Specifications

|              |                                          |
|--------------|------------------------------------------|
| Weight       | 1.49 kg                                  |
| Voltage      | 18 V DC                                  |
| Vibration    | 1.63 ± 1.5 m/s <sup>2</sup>              |
| Chuck Size   | 1/4" (6.3 mm)                            |
| Chuck Type   | Hexagonal                                |
| Application  | Plasterboard, wood, wood-based materials |
| Battery Type | Li-Ion                                   |

|                                    |                                                                                                           |
|------------------------------------|-----------------------------------------------------------------------------------------------------------|
| <b>Kit Contents</b>                | Single screw attachment, collated tape screw attachment, extension adapter, screwdriver bit, belt holster |
| <b>Acoustic Power</b>              | 80.0 ± 3.0 dB(A)                                                                                          |
| <b>Battery Included</b>            | No                                                                                                        |
| <b>Charger Included</b>            | No                                                                                                        |
| <b>Protection Class</b>            | IPX0                                                                                                      |
| <b>Rotational Speed</b>            | 0–4000 rpm                                                                                                |
| <b>Work Mode Switch</b>            | No                                                                                                        |
| <b>Acoustic Pressure</b>           | 72.0 ± 3.0 dB(A)                                                                                          |
| <b>Hammering Function</b>          | No                                                                                                        |
| <b>Collated Screw Length</b>       | 25–55 mm                                                                                                  |
| <b>Collated Screw Diameter</b>     | 3.5–4.2 mm                                                                                                |
| <b>Electric Insulation Class</b>   | III                                                                                                       |
| <b>Rotation Direction Switch</b>   | Yes                                                                                                       |
| <b>Electronic Speed Adjustment</b> | Yes                                                                                                       |

## Key Points

- Designed for drywall, wood, and wood-based materials — ideal for suspended ceilings, partition walls, and attic installations
- Rotational speed 0–4000 rpm for fast, precise screw driving
- Compatible with collated tape screws (Ø 3.5–4.2 mm, length 25–55 mm) and individual screws
- 1/4" (6.3 mm) hexagonal chuck with electronically adjustable speed and rotation direction switch
- Lightweight at 1.49 kg for reduced fatigue during prolonged use
- 18 V Li-Ion cordless design for full mobility — battery sold separately (body only version)
- Battery charge indicator for continuous energy level monitoring
- Kit includes: single screw attachment, collated tape screw attachment, extension adapter, and screwdriver bit
- Protection class IPX0; Electric insulation class III

## Warnings

- This is the body-only version (YT-82076) — no battery or charger included. Compatible 18 V Li-Ion battery and charger available separately (see YT-82075 for the full kit).
- Acoustic pressure level 72.0 dB(A) — hearing protection recommended during prolonged use.
- Vibration emission 1.63 m/s<sup>2</sup> — assess cumulative exposure to comply with local hand-arm vibration regulations.