

Yato | Code YT-90201 | Sku 1090201

Irrigation Controller



Overview

An advanced, two-way automatic irrigation controller with a large LCD screen and an easy-to-use adjustable knob. Independent control of two watering zones makes it an ideal solution for larger gardens or crops. Programming the frequency and duration of watering cycles allows for efficient and economical water management, facilitating daily plant care. Features include: two-way digital irrigation controller; clear LCD screen and convenient adjustment knob for easy and quick operation; ability to program up to 6 watering cycles per day for each zone; working time from 1 minute to 6 hours for flexible adjustment of watering intensity; independent operation of two valves to save time and water; delay start function for improved water management efficiency; manual control for full override of the irrigation process; battery level monitoring to reduce the risk of unexpected shutdown. Power supply: 2 × AA 1.5 V batteries (not included). Includes a faucet adapter with 3/4" and 1" reduction. Made from durable materials resistant to external and weather factors: ABS, POM, PC. Suitable for watering two independent garden zones, large plots, backyard gardens, greenhouses, flower beds, lawns, and vegetable crops.

Key Technical Specifications

Timer	Yes
Weight	0.47 kg
Material	ABS, PC, POM
Functions	Delayed start time
Battery type	2 × 1.5 V AA
Control type	Manual
Display type	LCD
Power supply	Battery
Working mode	Automatic, manual
Working time	1–360 min
Low battery indicator	Yes

Water outlet diameter	Inlet: 3/4" (19.0 mm), 1" (25.0 mm); Outlet: 3/4" (19.0 mm) × 2
Max. water temperature	50 °C
Max. operating pressure	6 bar
Electrical insulation class	III
Operating temperature range	5–40 °C

Key Points

- Two-way digital irrigation controller with independent control of two watering zones
- Large LCD screen and convenient adjustment knob for easy, quick operation
- Program up to 6 watering cycles per day per zone for an effective watering schedule
- Adjustable working time from 1 minute to 6 hours (1–360 min)
- Delay start function increases water management efficiency (e.g. during rainfall)
- Manual control provides full override of the irrigation process
- Battery level monitoring reduces risk of unexpected shutdown
- Powered by 2 × AA 1.5 V batteries (not included)
- Includes faucet adapter with 3/4" and 1" reduction
- Durable ABS, POM, and PC construction resistant to weather and external factors
- Max. operating pressure: 6 bar; max. water temperature: 50 °C
- Ideal for gardens, greenhouses, flower beds, lawns, and vegetable crops

Warnings

- Batteries (2 × AA 1.5 V) are not included.
- Do not exceed max. operating pressure of 6 bar or max. water temperature of 50 °C.
- For use within operating temperature range of 5–40 °C only.