

Yato | Code YT-0990 | Sku 100990

Pneumatic Air Hammer YT-0990



Overview

The pneumatic hammer YT-0990 is a professional solution for demanding tasks, enabling precise cutting, chiseling, and surface piercing. Powered by compressed air for optimal performance, it features a clamping spring for safe and stable operation. Compatible with chisels and piercers, it connects easily to any standard pneumatic system. The aluminum housing keeps the tool lightweight yet durable. Supplied as a comprehensive ready-to-use set.

Key Technical Specifications

|                                |                                                            |
|--------------------------------|------------------------------------------------------------|
| Weight                         | 1.5 kg                                                     |
| Vibrations                     | 2.62 ± 9.1 m/s <sup>2</sup>                                |
| Holder Size                    | 10 mm                                                      |
| Set Includes                   | air hammer, hose connector, spring, chisels and punches x4 |
| Acoustic Power                 | 107.7 ± 2.5 dB(A)                                          |
| Housing Material               | aluminum                                                   |
| Impact Frequency               | 3200 min <sup>1</sup>                                      |
| Required Airflow               | 113 l/min                                                  |
| Acoustic Pressure              | 96.3 ± 1.3 dB(A)                                           |
| Air Connection Diameter        | standard (PT)                                              |
| Maximum Operating Pressure     | 0.7 MPa                                                    |
| Air Supply Hose Inner Diameter | 3/8" (9.5 mm)                                              |

Key Points

- Efficient metal cutting with precise chiseling capability
- Effective surface piercing using included chisels and piercers
- Powered by compressed air at up to 0.7 MPa operating pressure
- High impact frequency of 3200 strokes/min for productive work

- Lightweight aluminum housing weighing only 1.5 kg
- Clamping spring ensures safe and stable tool retention
- Comprehensive set: hammer, hose connector, spring, and 4 chisels/piercers included
- Standard 3/8" (9.5 mm) air supply hose connection

## Warnings

- High acoustic pressure (96.3 dB(A)) and acoustic power (107.7 dB(A)) — use appropriate hearing protection during operation.
- Vibration level  $2.62 \pm 9.1 \text{ m/s}^2$  — prolonged use may cause hand-arm vibration syndrome; follow applicable exposure limits.
- Do not exceed maximum operating pressure of 0.7 MPa.