

Fischer | Code 545685 | Sku 33952

fischer Plasterboard fixing DuoBlade WH K NV with angle hook

Overview

The fischer DuoBlade is part of the innovative DuoLine and therefore consists of different components, which enable the best possible performance. The self-drilling tip allows a clean and effective drilling procedure. The fixing is screwed in the pre-positioned installation with the (cordless) screwdriver setting tool flush to the surface of the gypsum plasterboard. The fischer DuoBlade is adapted for wood, metal and chipboard screws from 4 to 5 mm thickness as well as different hooks and eye screws. Consequently, it is universally suitable for fixing e.g. smoke detectors, curtain rods and shutters securely and quickly. The DuoBlade is placed in the plasterboard with a conventional PZ 2 drive. No special setting device is required.

Top Features

- High torque when anchor is installed for the feelgood-factor and an optimum feeling when setting.
- Anti rotation lock prevents from spinning in the drill hole.
- Use of commercially available hooks, screws and eyelets.
- PZ2 drive - same drive for plug and screw.
- Self-drilling plasterboard plug for fast and easy installation.
- Including screw with round hook.

Technical data

Amount	6 pcs
Contents	6 x DuoBlade6 x angle hook
Anchor length	44 mm
Anchorage depth	9.5 - 25 mm
GTIN (EAN-Code)	4048962323801
Min. bolt penetration	28 mm
Anchor length without drill tip	29 mm
Max. load in gypsum fibreboard 12.5 mm	34 kg
Max. load in gypsum plasterboard 9.5 mm	8 kg
Max. load in gypsum plasterboard 12.5 mm	10 kg
Min. thickness to first supporting layer	50 mm
Max. load in gypsum plasterboard 2x12.5 mm	20 kg

