

Yato | Code YT-09505 | Sku 100950

Twin Hammer Pneumatic Impact Wrench 1/2" 570 Nm



Overview

The YT-09505 pneumatic impact wrench combines innovative TWIN HAMMER technology with a solid composite and duralumin construction, delivering high efficiency and long service life. With a maximum torque of 570 Nm and a no-load speed of 10,000 rpm, it handles even the most stubborn fasteners with ease. The lightweight design at only 1.4 kg reduces operator fatigue during extended use. Ideal for industrial applications, mechanical workshops, and automotive services.

Key Technical Specifications

Length	170 mm
Weight	1.4 kg
Vibration	3.0 ± 1.5 m/s ²
Drive Size	1/2" (12.7 mm)
Application	Industry, mechanical workshops, automotive services
Max. Torque	570 Nm
Set Includes	Pneumatic wrench, hose connector
No-Load Speed	10,000 min ¹
Acoustic Power	101.7 ± 3.0 dB(A)
Casing Material	Composite, duralumin
Direction Switch	Yes
Tool Holder Type	Driver
Acoustic Pressure	97.0 ± 3.0 dB(A)
Required Air Flow	142 l/min
Quick Coupler Size	Standard
Impact Mechanism Type	TWIN HAMMER
Max. Working Pressure	0.63 MPa
Air Connection Diameter (PT)	Standard

Air Supply Hose Inner Diameter	3/8" (9.5 mm)
---------------------------------------	---------------

Key Points

- TWIN HAMMER impact mechanism for high efficiency and outstanding durability
- Maximum torque of 570 Nm for easy removal of stubborn screws and nuts
- High no-load speed of 10,000 rpm for increased productivity
- Lightweight design at only 1.4 kg to reduce operator fatigue
- Durable composite and duralumin casing for exceptional resistance to damage
- Built-in direction switch for precise maneuvering
- 1/2" (12.7 mm) square drive
- Includes pneumatic wrench and hose connector

Warnings

- Acoustic pressure level 97.0 dB(A) — hearing protection recommended during use
- Vibration level 3.0 m/s² — monitor daily exposure time to comply with occupational health regulations