

Yato | Code YT-07535 | Sku 1007535

DIGITAL TORQUE ADAPTER 1/2" 10-200NM



Overview

Unmatched precision and versatility of applications. Achieve the perfect torque with the YT-07535 adapter. An indispensable tool for professionals and DIY enthusiasts. Reliability in your workshop. Precise setting of the expected torque. Wide working range from 10 to 200 Nm suitable for many tasks. High measurement accuracy with a tolerance of just +/- 2%. Versatility thanks to included reductions from 1/2" to 3/8" and 1/4". Clear color LCD display for quick reading. Ability to work in a wide temperature range (0-40C). Compatibility with various socket sizes for greater universality. Practical battery power for mobility. Key technical parameters: Torque range: 10-200 Nm. Measurement tolerance: ±2%. Tool holder size: 1/2" (12.7 mm). Socket sizes: 1/4" (6.3 mm), 3/8" (9.5 mm), 1/2" (12.7 mm). Display type: Color LCD. Power supply: Battery, 2x AAA 1.5 V. Included reductions: 1/2" (F) x 3/8" (M), 1/2" (F) x 1/4" (M). Included HEX key. Operating temperature range: 0-40C. Storage temperature: -10 to +50C. Relative operating humidity: <80% Rh. Device weight: 172g.

Key Technical Specifications

Brand	Yato
Symbol	YT-07535
Torque	10-200 Nm
Weight	172 g
Cell type	2x1.5V; AAA
Tolerance	±2 %
Holder size	1/2" (12.7 mm)
Display type	LCD
Power supply	battery
Producer code	5906083081613
Drive adapter size	1/4" (6.3 mm), 3/8" (9.5 mm), 1/2" (12.7 mm)
Storage temperature	-10 ~ +50 C

Working temperature range 0–40 C

Operating relative humidity Rh <80 %

Key Points

- Precise setting of the expected torque
- Wide working range from 10 to 200 Nm suitable for many tasks
- High measurement accuracy with a tolerance of just +/- 2%
- Versatility thanks to included reductions from 1/2" to 3/8" and 1/4"
- Clear color LCD display for quick reading
- Ability to work in a wide temperature range (0-40C)
- Compatibility with various socket sizes for greater universality
- Practical battery power for mobility
- Torque range: 10-200 Nm
- Measurement tolerance: $\pm 2\%$
- Tool holder size: 1/2" (12.7 mm)
- Socket sizes: 1/4" (6.3 mm), 3/8" (9.5 mm), 1/2" (12.7 mm)
- Display type: Color LCD
- Power supply: Battery, 2x AAA 1.5 V
- Included reductions: 1/2" (F) x 3/8" (M), 1/2" (F) x 1/4" (M)
- Included HEX key
- Operating temperature range: 0-40C
- Storage temperature: -10 to +50C
- Relative operating humidity: <80% Rh
- Device weight: 172g