

Yato | Code YT-90200 | Sku 1090200

IRRIGATION CONTROLLER



Overview

Modern and intuitive controller for automatic garden watering management. It allows precise setting of the frequency and duration of irrigation cycles, enabling effective and water-saving management. It works perfectly in home gardens and greenhouses, for lawns, flower beds, and vegetable patches. Manual control and automatic operation mode facilitate daily plant care. Product features: automatic digital controller; large LCD screen and convenient control knob make the controller easy and quick to operate; possibility to program up to 6 watering cycles per day, allowing you to adjust the irrigation schedule to plant species, their growth phases, or weather conditions; working time from 1 minute to 6 hours allows flexible adaptation to specific areas and types of crops; delay start function increases water management efficiency, saving water e.g. during rainfall; manual control ensures control over the irrigation process; battery level monitoring reduces the risk of unexpected shutdown; power supply: 2 AA 1.5 V batteries (not included); adapter for faucet with 3/4" and 1" reduction; durable materials, resistant to external and weather factors: ABS, POM, PC; max. working pressure: 6 bar; max. water temperature: 50C; operating temperature: 5-40C; weight: 0.31 kg. Application: automatic watering of vegetable patches, flower beds, lawns; ideal for greenhouses, drip irrigation systems, and sprinklers; an economical solution saving water and time; facilitates garden care even in the absence of household members.

Key Technical Specifications

Brand	Yato
Symbol	YT-90200
Weight	0.31 kg
Material	ABS, P.C, POM
Cell type	2x1.5V; AA
Functions	delayed start time
Control type	manual

Display type	LCD
Power supply	battery
Working mode	automatic, manual
Working time	1-360 min
Producer code	5906083119149
Time setting (timer)	yes
Low battery indicator	yes
Water outlet diameter	inlet: 3/4" (19.0 mm), 1" (25.0 mm), outlet: 3/4" (19.0 mm)
Max. water temperature	50 C
Max. operating pressure	6 bar
Electric insulation class	III
Working temperature range	5~40 C

Key Points

- Automatic digital controller
- Large LCD screen and convenient control knob for easy and quick operation
- Programmable up to 6 watering cycles per day to suit plant species, growth phases or weather conditions
- Working time from 1 minute to 6 hours for flexible adaptation to specific areas and crops
- Delay start function saves water, e.g. during rainfall
- Manual control for direct oversight of the irrigation process
- Battery level monitoring reduces the risk of unexpected shutdown
- Power supply: 2 AA 1.5 V batteries (not included)
- Faucet adapter with 3/4" and 1" reduction
- Durable materials resistant to weather factors: ABS, POM, PC
- Max. working pressure: 6 bar
- Max. water temperature: 50C
- Operating temperature: 5-40C
- Weight: 0.31 kg
- Ideal for greenhouses, drip irrigation systems and sprinklers

Warnings

- Batteries not included (requires 2 AA 1.5 V batteries)
- Do not exceed max. working pressure of 6 bar
- Do not exceed max. water temperature of 50C
- Use only within the operating temperature range of 5-40C