

Yato | Code YT-4075 | Sku 104075

Twist Drill Bit HSS-CO, 7.5 mm



Overview

HSS-E Co (HS6-5-2-5) twist drill bit with a diameter of 7.5 mm and a cylindrical toolholder, designed for drilling stainless steel, acid-resistant steel, cast iron, non-ferrous metals and plastic. Features a polished surface finish, a 135° split point and high temperature resistance. Compliant with DIN 338 and PN-EN ISO 4957:2002(U). Usage warnings: Warning! Always use personal safety equipment at work.

Key Technical Specifications

DIN	338
Pcs	1
Brand	Yato
Symbol	YT-4075
Diameter	7.5 mm
Material	HSS-E Co HS6-5-2-5
Standard	PN-EN ISO 4957:2002(U)
Application	stainless steel, stainless steel, acid-resistant steel, cast iron, non-ferrous metals, plastic
Split point	yes
Producer code	5906083940750
Overall length	109 mm
Finish	polished, polished
Toolholder type	cylindrical
Tensile strength	>900 N/mm ²
Working part length	69 mm
Drill bit point angle	135
High temperature resistance	yes

Key Points

- Diameter: 7.5 mm; overall length: 109 mm; working part length: 69 mm
- Made of HSS-E Co (HS6-5-2-5) with tensile strength >900 N/mm²
- 135° split point for accurate, self-centering drilling
- Polished surface finish and high temperature resistance
- Cylindrical toolholder; complies with DIN 338 and PN-EN ISO 4957:2002(U)
- Suitable for stainless steel, acid-resistant steel, cast iron, non-ferrous metals and plastic

Warnings

- Warning! Always use personal safety equipment at work.