

Yato | Code YT-73275 | Sku 1073275

ELECTRONIC PLATFORM SCALE 100KG/20G



Overview

The durable electronic platform scale with a measuring accuracy of 20 g is designed for weighing larger loads up to 100 kg. The weighing surface of 300 x 400 mm made of carbon steel provides stability and resistance to loads. The ABS body with dust cover protects components from dirt and mechanical damage. The device is equipped with a one-sided LCD display with LED backlight, ensuring excellent readability of readings in any lighting conditions. An acrylic panel with 24 PVC buttons allows for intuitive operation, and built-in functions - zeroing, taring, mass stabilization, and overload warning - facilitate daily work. The scale is powered by a 4 Ah lead-acid battery. The charger included in the set allows for convenient use without constant connection to the power supply. With a low weight of 5 kg, it is easy to carry and place in any work station. measuring accuracy: 20 g; one-sided LCD display with LED backlight; acrylic panel with 24 PVC buttons; functions: zeroing, taring, mass stabilization, overload warnings; power supply: 4 Ah lead-acid battery, 4 V, 16 Wh; max. load: 100 kg; material: carbon steel; ABS body and cover made of durable and resistant material; weighing surface: 300 x 400 mm; storage temperature: 0-50C; working temperature: 5-35C; relative humidity Rh: <=90%; rated current: 0.3 A; body with dust cover; weight: 5 kg; charger included in the set. *It is not a measuring device within the meaning of the "Weights and Measures Act".

Key Technical Specifications

Fold	no
Brand	Yato
Symbol	YT-73275
Weight	5 kg
Voltage	220-240 V a.c.
Frequency	50/60 Hz
Functions	calibrating, taring, stabilisation of the weight indication, overload warnings

Scale area	300x400 mm
Battery type	lead-acid
Display type	LCD
LED backlight	yes
Producer code	5906083122514
Battery energy	16 Wh
Battery voltage	4 V d.c.
Nominal current	0.3 A
Battery capacity	4000 mAh
Charger included	yes
Protection grade	IPX0
Max. load capacity	100 kg
Storage temperature	0~50 C
Measurement accuracy	20 g
Low battery indicator	no
Operating relative humidity Rh	<=90 %
Operating temperature at a site	5~35 C

Key Points

- Measuring accuracy: 20 g
- One-sided LCD display with LED backlight
- Acrylic panel with 24 PVC buttons
- Functions: zeroing, taring, mass stabilization, overload warnings
- Power supply: 4 Ah lead-acid battery, 4 V, 16 Wh
- Max. load: 100 kg
- Weighing surface made of carbon steel: 300 x 400 mm
- ABS body and cover with dust cover
- Storage temperature: 0-50 C, working temperature: 5-35 C
- Rated current: 0.3 A
- Weight: 5 kg
- Charger included in the set

Warnings

- This is not a measuring device within the meaning of the "Weights and Measures Act".
- Protection grade IPX0 - not protected against water ingress.