

Yato | Code YT-67564 | Sku 1067564

Bearing Caulking Gun 15"/380mm



Overview

The bearing-mounted thick material extruder is a professional tool that ensures precise application of adhesives, silicones, or sealants. Thanks to its solid aluminum construction and the use of up to 13 bearings, the plunger moves smoothly, minimizing effort during work and increasing the precision of material dosing. It features automatic glue flow cut-off thanks to a shut-off valve on the body, allowing for immediate stopping of the material stream, resulting in significant savings and waste reduction. The safety valve increases control over the tool's operation and protects against accidental material leakage. The 360° rotation of the body allows for maneuvering and precise material application in hard-to-reach areas. Technical data: tube length: 380 mm tube capacity: 600 ml dimensions: 535 x 215 mm outer diameter: 67 mm inner diameter: 51 mm material: aluminum

Key Technical Specifications

Lock	yes
Size	535x215 mm
Type	gutter, strengthened
Brand	Yato
Rotary	yes
Symbol	YT-67564
Bearing	yes
Material	aluminum
Functions	automatic glue flow cut-off, shut-off valve on the body, switchable safety valve
Application	dense masses, glues, silicones, sealants, renovation and finishing works
Tube length	380 mm
Bearing type	ball

Producer code	5906083123801
Tube capacity	600 ml
External diameter	67 mm
Internal diameter	51 mm

Key Points

- Bearing-mounted plunger construction - 13 precision bearings ensure smooth plunger movement, reducing the force needed to extrude material and guaranteeing a uniform, controlled material flow
- Automatic glue flow cut-off - immediately stops the material from flowing out after releasing pressure, reducing waste and increasing material savings
- Shut-off valve on the body - provides additional control over material flow and quick flow stoppage at any time
- Switchable safety valve - protects against accidental material leakage and increases precision during work
- 360° body rotation - allows for comfortable tool maneuvering, enabling precise material application in hard-to-reach areas
- Solid, lightweight aluminum construction for durability and user comfort
- Standard size 380 mm - compatible with most sealants and adhesives used in professional and home projects
- Tube capacity: 600 ml