

Yato | Code YT-01344 | Sku 1001344

FLARE NUT RATCHET WRENCH SET 8-19MM 6PCS



Overview

Set of semi-open ratchet wrenches designed for quick loosening and tightening of screw connections, especially in areas with limited working space. The use of a 72-tooth ratchet mechanism allows for a small working angle and eliminates the need to remove the wrench from the nut with each movement, which speeds up vehicle servicing, installation assembly, or mechanical work. The body is made of chromium-vanadium steel (CrV) with a hardness of 42-49 HRC, ensuring good strength and wear resistance. The As-Drive working profile increases the contact surface with the fastener, reducing the risk of damaging the edges of the screw, while the satin finish improves grip and protects the tool from corrosion. Key features and specifications: 72T ratchet mechanism – small working stroke allows for comfortable operation in hard-to-reach places; CrV steel – high-quality material resistant to loads and wear; Hardness 42-49 HRC – appropriate strength while maintaining material flexibility; As-Drive working profile – better torque transfer and edge protection for screws; Semi-open design – facilitates quick placement of the wrench on the fastener; Satin surface – reduces reflections and improves grip. 6 available sizes: 8 mm x 160 mm, 10 mm x 160 mm, 13 mm x 189 mm, 14 mm x 189 mm, 17 mm x 215 mm, 19 mm x 230 mm.

Key Technical Specifications

Pcs	6
Size	8, 10, 13, 14, 17, 19 mm
Type	semi-open
Brand	Yato
Symbol	YT-01344
Ratchet	yes
AS-DRIVE	yes
Hardness	42-49 HRC
Material	CrV

Application	service, workshop
Head coating	satın
Producer code	5906083124822
Overall length	160, 160, 189, 189, 215, 230 mm
Finish	chrome plated, satin
Number of teeth	72
Rotation switch	no
Ring wrench type	hexagonal
Min. operation angle	5

Key Points

- 72T ratchet mechanism – small working stroke allows for comfortable operation in hard-to-reach places
- CrV steel – high-quality material resistant to loads and wear
- Hardness 42-49 HRC – appropriate strength while maintaining material flexibility
- As-Drive working profile – better torque transfer and edge protection for screws
- Semi-open design – facilitates quick placement of the wrench on the fastener
- Satin surface – reduces reflections and improves grip
- 6 available sizes: 8 mm x 160 mm, 10 mm x 160 mm, 13 mm x 189 mm, 14 mm x 189 mm, 17 mm x 215 mm, 19 mm x 230 mm

Warnings

- Always use personal safety equipment at work.