Technical Data Sheet

Yato | Code YT-24240 | Sku 1024240

Pneumatic Hose Reel



Overview

Order and efficiency in the workshop. Ensure maximum comfort and order with the pneumatic hose YT-24240 on a reel. The 15-meter length guarantees freedom of movement in any workshop. Professionalism and order, high resistance to stretching and abrasion, exceptional resistance to aggressive chemicals, long lifespan due to material aging resistance, smooth and precise winding adjustment for comfortable work, universal wall or floor mounting for stability, standard quick couplings for rapid connection, increased scratch resistance for long-term use, internal diameter of 10 mm ensuring optimal airflow, high flexibility, reel included, standard quick couplings, 15-meter length, professional application. Technical data: Conduit material: PVC; Conduit length: 15 meters; Connection hose length: 0.6 meters; Internal hose diameter: 10 mm; Maximum air pressure: 2 bar; Air connection diameter: Standard (PT). Included in the set: 15 m pneumatic hose on reel, 0.6 m connection hose, reel with crank, mounting anchors x4 (for floor or wall).

Key Technical Specifications

Brand	Yato
Length	15
Symbol	YT-24240
Material	PVC
Hose length	m
Set includes	pneumatic hose, connection cable, reel with crank, fixing anchors x4
Producer code	5906083011641
Air inlet length	0.6 m
Hose auto rewind	no
Internal diameter	10 mm
Max. air pressure	2 MPa
Scratch resistant	yes

Chemical resistance	yes
Air connection diameter (PT)	standard

Key Points

- High resistance to stretching and abrasion
- Exceptional resistance to aggressive chemicals
- Long lifespan due to material aging resistance
- Smooth and precise winding adjustment for comfortable work
- Universal wall or floor mounting for stability
- Standard quick couplings for rapid connection
- Increased scratch resistance for long-term use
- Internal diameter of 10 mm ensuring optimal airflow
- Conduit material: PVC
- Conduit length: 15 meters
- Connection hose length: 0.6 meters
- Internal hose diameter: 10 mm
- Maximum air pressure: 2 bar
- Air connection diameter: Standard (PT)
- 15 m pneumatic hose on reel
- 0.6 m connection hose
- Reel with crank
- Mounting anchors x4 (for floor or wall)