

Technical Data Sheet

Yato | Code YT-38872 | Sku 1038872

Yato TOOL SET YT-38872



Specifications

Pieces	128
Brand	Yato
Symbol	YT-38872
AS-DRIVE	yes
Material	CRV 6150, CrV 50BV30, CrMo SCM-440, S2
Application	car services, mechanical services, industry, household
Holder Size	1/4" (6.3 mm), 3/8" (9.5 mm), 1/2" (12.7 mm)
Producer Code	5906083388729
Number of Teeth	72

Features

- Made of durable tool steel, ensuring long life
- Enables work requiring very high loads and precision
- Forged and precisely calibrated sockets for perfect fit
- AS-Drive system increasing maximum torque by 25% with full nut edge protection
- Bits made of hard S2 steel, ensuring durability
- Ratchets with a three-component handle and 72 teeth (5-degree working stroke) for comfort and precision
- Two-tone finish of socket surfaces emphasizing professionalism
- Materials: CrV 6150, CrV 50BV30, CrMo SCM-440, S2
- Ratchet teeth count: 72
- AS-DRIVE system: Yes
- Tool handle size: 1/4" (6.3 mm), 3/8" (9.5 mm), 1/2" (12.7 mm)
- Number of pieces in the set: 128

Technical Data Sheet

Applications

- Ideal for many service activities related to threaded connections
- Application: car workshops, mechanical workshops, industry, household

What's Included

- Sockets:
 - 1/2" (12.7 mm): 14, 15, 16, 17, 18, 19, 20, 21, 22, 24 mm (L=38 mm); 27, 30, 32 mm (L=42 mm)
 - 3/8" (9.5 mm): 10, 11, 12, 13, 14, 15, 16 mm (L=28 mm); 17, 18 mm (L=30 mm)
 - 1/4" (6.3 mm): 6, 7, 8, 9, 10, 11, 12, 13 mm (L=25 mm)
- Long sockets:
 - 1/2" (12.7 mm): 17, 18, 19, 22 mm (L=76 mm)
 - 3/8" (9.5 mm): 8, 10, 12, 13, 14, 15 mm (L=63 mm)
 - 1/4" (6.3 mm): 6, 7, 8, 10, 12, 13 mm (L=50 mm)
- Sockets: 1/2" (12.7 mm): 17, 19, 21, 22 mm
- Sockets 3/8" (9.5 mm): E8, E10, E11, E12, E14, E16
- Extensions:
 - 1/2" (12.7 mm): 127 mm, 254 mm
 - 3/8" (9.5 mm): 152.4 mm, 254 mm
 - 1/4" (6.3 mm): 50.8 mm, 101.6 mm
 - 3/8" (9.5 mm) to 1/2" (12.7 mm) adapter
- Cardan joints: 1/2" (12.7 mm), 3/8" (9.5 mm), 1/4" (6.3 mm)
- Sockets for spark plugs 1/2" (12.7 mm): 16, 21 mm
- T-handles:
 - 3/8" (9.5 mm): 198 mm
 - 1/4" (6.3 mm): 152.4 mm
- Ratchets:
 - 1/2" (12.7 mm): 255 mm; 72T
 - 3/8" (9.5 mm): 200 mm; 72T
 - 1/4" (6.3 mm): 155 mm; 72T
- Socket handle 1/4" (6.3 mm); (150 mm)
- L-type handles: 1/2" (12.7 mm): 250 mm
- Adapters:
 - 3/8" (9.5 mm) x 5/16" (7.9 mm)
 - 1/2" (12.7 mm) x 3/8" (9.5 mm)
 - 3/8" (9.5 mm) x 1/4" (6.3 mm)
 - 1/4" (6.3 mm) x 1/4" (6.3 mm); CrV 50BV30;
- Bits:
 - Flat 3/8" (9.5 mm): 5.5, 6.5 mm (L=70 mm)
 - Phillips 3/8" (9.5 mm): PH1, PH2, PH3 (L=70 mm)
 - Torx 3/8" (9.5 mm): T20, T30, T40, T45, T50, T55 (L=70 mm)
 - Hex 3/8" (9.5 mm): 6, 7, 8, 10, 12 mm (L=70 mm)

Technical Data Sheet

- Pozidrive 1/4" (6.3 mm): PZ1, PZ2 (L=25 mm)
- Torx 1/4" (6.3 mm): T8, T10 (L=25 mm)
- Socket bits:
- Flat 1/4" (6.3 mm): 4, 5.5, 6.5 mm (L=37 mm)
- Phillips 1/4" (6.3 mm): PH1, PH2 (L=37 mm)
- Torx 1/4" (6.3 mm): T8, T10, T15, T20, T25, T30, T40 (L=37 mm)
- Hex 1/4" (6.3 mm): 3, 4, 5, 6 mm (L=37 mm)
- Open-end wrenches: 8, 10, 12, 13, 14, 15, 16, 17, 18, 19 mm
- Hex keys: 1.5, 2, 2.5 mm