



Impact Driver LXT®

DTD134RFE

14,4V • 1/4" • 155 Nm • 0 - 2 400 min⁻¹

Very light Impact Driver

Rubberized soft grip provides increased comfort on the job. Extreme Protection Technology (XPT) is engineered for increased dust and water resistance for operation in harsh job site conditions. Variable speed (0-2,400 RPM & 0-3,200 IPM) provides 155 N·m (1,370 in.lbs.) of Max Torque for a wide range of fastening applications. Includes 2 x 3,0 Ah batteries and a charger in a case.



TECHNICAL SPECIFICATIONS

max fastening torque impact drill	155 Nm
No load speed	0-2400 min ⁻¹
Impact	0-3200 min ⁻¹
Tightening Capacity Standard Bolt	M5 - M14
Capacity machine screw	M4-M8
Tightening Capacity High Tensile Bolt	M5 - M12
Battery protection	✓
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Vibration Level (3 axes)	12 m/s ²
Vibration Uncertainty (K Factor)	1,5 m/s ²
Sound Power Level (L _{WA})	103 dB(A)
Sound Pressure Level (L _{pA})	92 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Tool weight with battery (EPTA)	1.2 - 1.4. kg

USER BENEFITS

- Battery level indicator
- LED light illuminates the work site

EAN 0088381663069

Link to Product page - www.makita.ae



RELATED PRODUCTS

OPTIONAL ACCESSORIES

821550-0
Makpac case (2)



OTHER

User manual

