

Makita | Code DHR263Z | Sku 85986

Combination Hammer LXT®

Key Technical Specifications

IMPACT	0 - 5000 min ¹
SIDE GRIP	Yes
VOLTAGE LXT	Yes
IMPACT ENERGY	2,5 J
NO LOAD SPEED	0 - 1250 min ¹
BATTERY PROTECTION	Yes
VIBRATION: CHISELLING	14 m/s ²
NOMINAL BATTERY VOLTAGE	2 x 18 V
SOUND POWER LEVEL (LWA)	102 dB(A)
SOUND PRESSURE LEVEL (LPA)	94 dB(A)
NOISE UNCERTAINTY (K FACTOR)	3 dB(A)
MAX. DRILLING DIAMETER IN WOOD	32 mm
MAX. DRILLING DIAMETER IN STEEL	13 mm
PRODUCT DIMENSIONS (L X W X H):	350 x 116 x 232 mm
TOOL WEIGHT WITH BATTERY (EPTA)	3,5 - 4,7 kg
VIBRATION UNCERTAINTY (K FACTOR)	1,5 m/s ²
MAX. DRILLING DIAMETER IN CONCRETE	26 mm
VIBRATION LEVEL (3 AXES), DRILLING	3,0 m/s ²
DRILLING DIAMETER WITH TCT CORE BIT	54 mm
VIBRATION LEVEL (3 AXES), IMPACT DRILLING	14,5 m/s ²
OPTIMUM DRILLING DIAMETER RANGE IN CONCRETE	6 - 16 mm